



Xitanium LED downlight and spotlight drivers

Xitanium 20W WH 0.15-0.5A 54V SR Is 230V

Xitanium LED drivers are leading the way in terms of reliability

Product data

General Information	
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	540 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	20 W
Output Power (Min)	6 W
Output Current (Min)	150 mA
Output Voltage (Max)	54 V
Output Voltage (Min)	24 V
Protection class IEC	Safety class I/II
System characteristics	
Central DC Operation	Yes
YellowDot ready	No
Temperature	
T-Case Lifetime (Max)	65 °C

T-Case Maximum (Max)	75 °C
Controls and Dimming	
Dimmable	DALI
Mechanical and Housing	
Product Length	200 mm
Overall length	201 mm
Overall width	75 mm
Overall height	32.5 mm
Dimensions (Height x Width x Depth)	33 x 75 x 201 mm
Ingress protection code	IP20 [Finger-protected]
Net Weight (Piece)	0.225 kg
Approval and Application	
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options	DALI, NFC

Xtanium LED downlight and spotlight drivers

Product Data

Order product name	Xtanium 20W WH 0.15-0.5A 54V SR Is 230V
Full product name	Xtanium 20W WH 0.15-0.5A 54V SR Is 230V
Full product code	871951432704700
Order code	929002861106
Material Nr. (12NC)	929002861106

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514327047
Numerator - Packs per outer box	12
EAN/UPC - Case	8719514327054

